

€€

SPLITTER BOX

PNSB



ACHIEVE MORE IN LESS TIME

The SA POWERNET EX Splitter Box safely provides four 16A socket outlets in any environment. The rugged, waterproof and dustproof design makes our box practically indestructible, and it's supplied ready for use in **full 'plug-and-play'** state. Available in a range of voltage options, and usually available for next-day delivery.

128



SPLITTER BOX PNSB

BENEFITS

- ATEX Certified for Zones 1 and 2 (gas), 21 and 22 (dust)
- Tough and durable
- Fast delivery times
- Waterproof and dustproof
- Compatible with SA lighting systems







You may also need...
Standard LED Worklights – see pages 60 & 64
Emergency LED Worklight – see page 68
Transformers – see pages 120 & 124
Extension Leads – see page 136

SPECIFICATIONS

CERTIFICATION

Ex tD A21 IP66 T85°C

CERTIFICATION (WITH STAHL SOCKETS)

INGRESS PROTECTION

1P66

OPERATING TEMPERATURE

-20°C to +40°C

VOLTAGE

110VAC, 230VAC

INPUT

1 x 16A Plug

OUTPUT

4 x 16A Socket Outlets

DIMENSIONS

450mm [w] x 450mm (d) x 200mm [h]

WEIGHT

6.6kg (without cable)

CABLE LENGTH

15m (or as required)

CORE PRODUCT INFORMATION

SA POWERNET EX Splitter Unit 4-way 110V c/w 1 x 16A CEAG plug, 4 x 16A CEAG sockets, and 15m of braided H0FR cable Order Code: PNSB110/15-4EX/CEA



SA POWERNET EX Splitter Unit 4-way 230V c/w 1 x 16A CEAG plug, 4 x 16A CEAG sockets, and 15m of braided HOFR cable Order Code: PNSB230/15-4EX/CEA



SA POWERNET EX Splitter Unit 4-way 110V c/w 1 x 16A STAHL plug, 4 x 16A STAHL sockets, and 15m of braided HOFR cable Order Code: PNSB110/15-4EX/STA



SA POWERNET EX Splitter Unit 4-way 230V c/w 1 x 16A STAHL plug, 4 x 16A STAHL sockets, and 15m of braided H0FR cable Order Code: PNSB230/15-4EX/STA



ATX connectors and different cable lengths also available – please contact SA Equip for more details.

See page 26 for our Plug, Socket, and Cable guide.

See pages 142 - 145 for the complete Core Product Directory.



























