



01619E00

- > For universal application
- > Versions with
 - snap-action contact
 - positive opening contact
- > With connecting cable or with single cores when it is used as a built-in device
- > Width
 - Single limit switch 11 mm
 - Double limit switch 15.5 mm



WebCode 8064A

Zone	ATEX / GOST					
	0	1	2	20	21	22
8064/1 with single cores: For use in		x	x			
8064/2 with connecting cable: For use in		x	x		x	x

Selection Table								
Version	Contacts	Connection cross-section	Cable length	Order number	Art. no.	PS	Weight kg	
<p>04362E00</p>	<p>07660E00</p>	Silver	Connecting cable, H05VV-F, 0.75 mm ²	3 m	8064/21-130-30-000	131486	17	0.210
	<p>07661E00</p>	Silver	Connecting cable, H05VV-F, 0.75 mm ²	2 m	8064/21-140-20-000	131492	17	0.160
	<p>07659E00</p>	Galvanically gold-plated silver	Connecting cable, H05VV-F, 0.75 mm ²	1 m	8064/21-320-10-000	131495	17	0.100
<p>04364E00</p>	<p>07658E00</p>	Silver	Connecting cable, H05VV-F, 0.75 mm ²	5 m	8064/21-110-50-102	131483	17	0.420
	<p>07660E00</p>	Silver	Connecting cable, H05VV-F, 0.75 mm ²	3 m	8064/21-130-30-102	131489	17	0.210
<p>04365E00</p>	<p>07660E00</p>	Silver	Connecting cable, H05VV-F, 0.75 mm ²	5 m	8064/21-130-50-103	131484	17	0.420